

# Extruded Rubber Wheel Chock 4-1/2 In. x 10 In. x 3-3/4 In. Black

## MODEL EX-4

Loading Dock Equipment / Rubber Wheel Chocks

### PRODUCT OVERVIEW

The rubber Wheel Chock is constructed of reinforced rubber to provide a sure grip on virtually any surface. The curved surface contours to fit tires. Rubber resists tearing, abrasion, ozone weathering, etc. The functional design is durable in all weather conditions.

### KEY FEATURES

- Reinforced rubber resists tearing, abrasion and ozone weathering
- Functional design is durable in all weather conditions
- Rubber provides a sure grip on virtually any surface
- Curved surface contours to fit any tire style

### CORE PRODUCT DATA

ASSEMBLED WEIGHT  
**5 lbs**

ASSEMBLED SIZE  
**10" W x 4.5" L x 3.75" H**

SHIP WEIGHT  
**5 lbs**

PACKAGE 1 SIZE  
**5" W x 12" D x 5" H**

COLOR / FINISH  
**Black**

FREIGHT TYPE  
**Parcel**

**AVAILABILITY** Available

**QUICKSHIP: YES**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

|                          |               |
|--------------------------|---------------|
| Wheel Chock Connection   | None          |
| Wheel Chock Usage        | Multi-Purpose |
| Built-In Handles / Poles | No            |
| Grip Surface Material    | Rubber        |
| Wheel Chock Quantity     | 1             |
| Rubber Type              | Extruded      |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 30 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=79>